

**Load table HFX/HFXE drivers**

Driver	Lamp	Load	Nominal input current at 230V	Inrush current /230V I <sub>peak</sub>	Inrush current (50% of I <sub>peak</sub> ) T <sub>width</sub>	Drivers per MCB							
						C10	C13	C16	C20	B10	B13	B16	B20
HFX 12918	T8	2x18W	0,16A	24A	<250µs	25	33	40	50	15	20	24	30
HFX 12936		2x36W	0,3A	24A	<250µs	25	33	40	50	15	20	24	30
HFX 12958		1x58W	0,5A	24A	<250µs	25	33	40	50	15	20	24	30
HFX 12949	LED	1x50W	0,24A	24A	<250µs	25	33	40	50	15	20	24	30
HFX 12951		1x25W	0,13A	24A	<250µs	25	33	40	50	15	20	24	30
HFXE 11918	T8	2x18W	0,17A	28A	<250µs	21	27	33	41	13	16	20	25
HFXE 11936		2x36W	0,32A	28A	<250µs	21	27	33	41	13	16	20	25
HFXE 11949	LED	1x50W	0,25A	28A	<250µs	21	27	33	41	13	16	20	25
HFXE 11951		1x25W	0,14A	28A	<250µs	21	27	33	41	13	16	20	25
HFX 16118	T8	1x18W	0,08A	33A	<250µs	19	24	30	38	11	15	18	23
HFX 16218		2x18W	0,15A	33A	<250µs	19	24	30	38	11	15	18	23
HFX 16136		1x36W	0,15A	33A	<250µs	19	24	30	38	11	15	18	23
HFX 16236		2x36W	0,3A	33A	<250µs	19	24	30	38	11	15	18	23
HFX 16158		1x58W	0,25A	33A	<250µs	19	24	30	38	11	15	18	23
HFX 16258		2x58W	0,5A	33A	<250µs	19	24	30	38	11	15	18	23
HFXE 12018	T8	1x18W	0,1A	47A	<250µs	13	17	21	26	8	11	13	16
HFXE 12618		2x18W	0,17A	47A	<250µs	13	17	21	26	8	11	13	16
HFXE 12036		1x36W	0,16A	47A	<250µs	13	17	21	26	8	11	13	16
HFXE 12673		2x36W	0,33A	47A	<250µs	13	17	21	26	8	11	13	16
HFXE 12058		1x58W	0,26A	47A	<250µs	13	17	21	26	8	11	13	16
HFXE 12658		2x58W	0,52A	47A	<250µs	13	17	21	26	8	11	13	16